




2/3" 1.4/25mm C		2/3"	1/1.8"	1/2"
FOCAL LENGTH		f=25mm		
MAX. DIAMETER (RATIO)		F=1:1.4~16		
ELEMENT		7 GROUPS 9 ELEMENTS		
PICTURE SIZE		6.6×8.8mm	5.4×7.2mm	4.8×6.4mm
ANGLE	VER. ANGLE	15.1°	12.4°	11.0°
	HOR. ANGLE	20.1°	16.5°	14.6°
	DIA. ANGLE	25.0°	20.6°	18.3°
DISTORTION (TV)		-0.3%		
SHOOTING RANGE AT MINIMUM FOCUS DISTANCE	VER.	84.5mm	69.0mm	61.2mm
	HOR.	113.3mm	92.4mm	82.0mm
	DIA.	142.5mm	116.0mm	102.8mm
MINIMUM FOCUS DISTANCE		0.3m		
FLANGE BACK		17.526mm in air		
BACK FOCUS		12.0mm in air		
FILTER SCREW SIZE		M30.5×0.5		
FRONT/REAR EFFECTIVE DIA.		FRONT ø23.7mm REAR ø14.4mm		
MOUNT		C-MOUNT		
EXIT PUPIL		-113.6mm		
TEMPERATURE RANGE		-10~+50°C		
STORAGE TEMPERATURE RANGE		-20~+60°C		
RESOLUTION CENTER/CORNER		CENTER 120本/mm CORNER 80本/mm		
WEIGHT		110 g		

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



		尺 度	1/1	工場 番号	1067NC
		機 種 名	2/3" F1.4 f=25mm		
2016.10.12	更新	機 種 番	LM25JC5M-IR		
2015.4.21	更新				
2010.10.2	作成年月日				