




2/3" 2.0/35mm C		2/3"	1/1.8"	1/2"
FOCAL LENGTH		f=35mm		
MAX. DIAMETER (RATIO)		F=2~16		
ELEMENT		7 GROUPS 9 ELEMENTS		
PICTURE SIZE		6.6×8.8mm	5.4×7.2mm	4.8×6.4mm
ANGLE	VER. ANGLE	10.8°	8.8°	7.8°
	HOR. ANGLE	14.3°	11.7°	10.4°
	DIA. ANGLE	17.8°	14.6°	13.0°
DISTORTION (TV)		0.05%		
SHOOTING RANGE AT MINIMUM FOCUS DISTANCE	VER.	17.6mm	14.4mm	12.8mm
	HOR.	23.4mm	19.2mm	17.0mm
	DIA.	29.4mm	24.0mm	21.3mm
MINIMUM FOCUS DISTANCE		0.1m		
FLANGE BACK		17.526mm in air		
BACK FOCUS		14.2mm in air		
FILTER SCREW SIZE		M34×0.5		
FRONT/REAR EFFECTIVE DIA.		FRONT φ23.0mm		REAR φ14.5mm
MOUNT		C-MOUNT		
EXIT PUPIL		-39.2mm		
TEMPERATURE RANGE		-10~+50° C		
STORAGE TEMPERATURE RANGE		-20~+60° C		
RESOLUTION CENTER/CORNER		CENTER 200lp/mm CORNER 140lp/mm		
LENS COATING		WIDE BAND MULTI COATING		
WEIGHT		160 g		

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



		尺 度	1/1	工場 番号	LR1014KW
		機 種 名	2/3" F2.0 f=35mm		
2014.12.25	更新	機 種 番	LM35JC10M 外觀図		
2013.4.15	作成年月日				