




2/3" 1.8/8mm C		2/3"	1/1.8"	1/2"
FOCAL LENGTH		f=8.5mm		
MAX. DIAMETER (RATIO)		F=1:1.8~22		
ELEMENT		9 GROUPS 11 ELEMENTS		
PICTURE SIZE		6.6x8.8mm	5.4x7.2mm	4.8x6.4mm
ANGLE	VER. ANGLE	41.9°	34.8°	31.2°
	HOR. ANGLE	54.0°	45.3°	40.8°
	DIA. ANGLE	64.6°	55.0°	49.7°
DISTORTION (TV)		0.31%		
SHOOTING RANGE AT MINIMUM FOCUS DISTANCE	VER.	99.6mm	81.3mm	72.2mm
	HOR.	133.2mm	108.7mm	96.5mm
	DIA.	166.5mm	136.3mm	121.0mm
MINIMUM FOCUS DISTANCE		0.1m		
FLANGE BACK		17.526mm in air		
BACK FOCUS		12.1mm in air		
FILTER SCREW SIZE		M34x0.5		
FRONT/REAR EFFECTIVE DIA.		FRONT φ26.7mm		REAR φ13.1mm
MOUNT		C-MOUNT		
EXIT PUPIL		-128.2		
TEMPERATURE RANGE		-10~+50°C		
STORAGE TEMPERATURE RANGE		-20~+60°C		
RESOLUTION CENTER/CORNER		CENTER 200lp/mm		CORNER 140lp/mm
LENS COATING		WIDE BAND MULTI COATING		
WEIGHT		115 g		

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



		尺度	1/1	工場番号	LR1010KW
		機種名	2/3" F1.8 f=8mm		
2014.12.25	更新	機種番	LM8JC10M 外観図		
2013.4.15	作成年月日				